

- The 690E is distinguished by its all new midnight blue case and includes a new ergonomically designed lay flat handle. An easy access storage compartment for reducers to freeze 8mm to 61mm runs along the top rear. The 690E case body has three openings where hoses and mains lead can be slotted so the machine can be used with the lid closed.
- Freeze Heads retain the original patented features and are designed to fit straight onto 2" Iron (61mm OD) with reducer fittings for 54mm 49mm 42mm 35mm 28mm 22mm & 15mm copper iron lead plastic etc. The 690E aluminium heads & reducers have a smart silver anodised finish. Spare reducer screws are supplied and stored in two panel fixings between the hose positions.
- <u>Active Capillary</u>. Of course, the reliable patented microprocessor controlled gas injection system is still at the heart of the Freeze Master. The new 690E chassis has updated electrical components.
- The 690E has new multilayer hoses with fittings and manifold attachments designed for the latest demands in cryogenic apparatus. Assembly of the 690E is carried out with the same strict attention to quality and control inculcated in the former design. Smaller, Lighter, yet just as powerful, the 690E is exactly what the market has been asking for.
- All machines are supplied with the recently invented Bungee Clamps (making them the most versatile to fit), freeze cream, insulating towels, gloves and fittings to freeze from 8mm to 61mm.

Capacity: 8/10/15/22/28/35/42/49/54/61 mm	Freeze time: 5 to 65 mins	Span: 3.9m
Dimensions: 390 X 300 X 355 mm	Refrigerant: R407c	Weight: 27 kg
Control: Active capillary (microprocessor)	240v model or 110v model	Power: 850 watts

Freeze Master 690E offers powerful, fast, electronically controlled freezing in a superbly engineered and constructed package. Available in 240V or 110V. The 690E will set the industry standard.

